



PH. 800-321-8073

[www.pittstrailers.com](http://www.pittstrailers.com)

FX. 334-855-3507

**Model CV42 – Chip Van – Closed Top**

**STANDARD FEATURES** **PLUS 12% FEDERAL EXCISE TAX**

Load Capacity _____	80,000 lbs.
Weight _____	11,600 lbs. +/- 3%
Overall Length _____	42'
Width _____	96"
King Pin Swing Radius _____	90"
King Pin Setting _____	36"
Upper Coupler Plate _____	Full Width w/ 1/4" Plate
Upper Coupler Height _____	48"
Landing Gear _____	Two Speed with Heavy Duty Bracing
Suspension _____	Hutch 3 Point, Four Spring w/ 14,000lbs Cap. Springs
Axles _____	(2)25K Cap.–Type 30 Chambers–Auto Slacks–ABS 16.5"x7" Brakes
Axle Width _____	8' Wide / 71 1/2" Track Axles
Axle Spacings _____	49" Spacings
Wheels _____	10 Hole Disc, Hub Piloted
Tires _____	11R24.5 Radials
Bottom Rail _____	Heavy Duty Fabricated Steel Rail w/ Bulb Design
Top Rail _____	Heavy Duty Extruded Aluminum Rail
Front Type _____	18" Diagonal
Front Material _____	.050 Natural Aluminum
Ladders _____	Steel Front
Rear Door Type _____	Heavy Duty Top 3 Hinged Chip Gate – Top Half Open for Blow In
Rear Door Material _____	Heavy Duty Steel Mesh
Side Sheet Material _____	.050 Natural Aluminum
Side Sheet Color _____	Natural Aluminum
Side Posts _____	Extruded Oval Shaped Aluminum on 16" Centers
Side Vents _____	5 Per Side – 12" in Height and Framed – Exp. Metal Vent Screen
Side Lining _____	Front & 2/3 Sides Covered w/ Heavy Duty Black Polyethylene
Top Lining _____	48" Wide – Full Length w/ Heavy Duty Black Polyethylene
Floor Type _____	Extruded Aluminum
Floor Sill Spacings _____	12" / 20" / 12" STD.
Parking Brakes _____	2 Axle
Dust Shields _____	None
Mud Flaps _____	Anti-Sail – Rear Frame
Bumper _____	3" x 4" Push Bumper
Wiring _____	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Lights _____	Sealed Wiring Harness with L.E.D. Package
Paint _____	Black (Two Part Primer w/ Two Part Polyurethane Paint)

\*\*\*NOTE\*\*\* ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

**OPTIONAL EQUIPMENT**

<b>BOGIE</b>		
Type 30/30 Spring Brakes (2 Axles Only) _____	add 40 lbs.	per axle
Single Point (2 Spring) Entire Length of Tandem Covered with Channel Iron _____	add 800 lbs.	
Air Ride Entire Length of Tandem Covered with Channel Iron _____	add 310 lbs.	
Air Lift One Axle _____	add 135 lbs.	
Pitts Lift Kit - Air Lift One Axle on a Single Point Suspension _____	add 95 lbs.	
Add a Third Axle (Spring Ride) _____	add 1,800 lbs.	
Add a Third Axle (Air Ride) _____	add 1,885 lbs.	
11R.22.5 Tires _____	deduct 88 lbs.	
425/60R22.5 Super Singles on Aluminum Disc Wheels _____	deduct 595 lbs.	
Aluminum Wheels (Inside Mill Finish & Outside Polished) _____	deduct 280 lbs.	
Tire Inflation System _____		
Onboard Electronic Scales (Trailer Only) (Vulcan or SI) _____	add 55 lbs.	
Onboard Air Scales (Trailer Only) _____	add 30 lbs.	
Air Gauge In Sealed Box _____		

**MISCELLANEOUS**

Winch Back Landing Gear _____		
8' 6" Wide Trailer / 96" Wide Axle _____	add 200 lbs.	
Heavy Duty Mesh Side Roll Tarp _____		
Heavy Duty Lock and Roll Tarp _____		
Side Flip Tarp System (Elect. Over Hyd.) _____		
Heavy Duty Barn Style Doors _____		
Hallco Mfg. - Walking Floor System - 4,000 Series - 3/16" Std. Ag Deck _____		
Keith Walking Floor System _____		
Revolver Greaseless Coupling System (Eliminates Need To Grease 5 <sup>th</sup> Wheel) _____	add 40 lbs.	
Additional Length _____	add 100 lbs.	per ft.
Additional Lights _____		Each
Special Paint Color (Any Color Other Than Black) _____		