



MODEL: LP40-4L 10,600 lbs.
LP40-4UL 9,850 lbs.

Model LP40-4UL

www.pittstrailers.com

STANDARD FEATURES	ULTRA LOAD PAYIN SERIES
-------------------	-------------------------

Load Capacity _____	80,000 lbs.
Weight _____	9,950 lbs.
Overall Length _____	40'
Width _____	8'6"
King Pin Swing Radius _____	84"
King Pin Setting _____	20"
King Pin Area _____	Covered With Two Hinged Tool Boxes
Fifth Wheel Height _____	48"
Mainframe _____	21" Fabricated - T1 Steel - 4" drop Center
Cross Members _____	Channel Iron w/ "X" Members
Bumper _____	Extended Push Bumper, 4"x 6"x 102"
Drag Bar _____	Braced to Back Bolster
Bolsters _____	3.5"x 10"x 102", High Yield Steel
Standards _____	4.5"x 4.5", T1 Steel, 13'4" Overall
Landing Gear _____	Heavy Duty Winch Forward, 7" Foot
Tandem _____	Entire Length of Tandem Covered with Channel Iron
Winches _____	With Four 30' Straps
Suspension _____	Hutch 3 Point, Four Spring w/ 14,000lbs. cap. Springs
Axles _____	25,000 lbs. cap. 77.5" Track, Auto Slack Adjusters, Type 30 Brake Chambers, 16 1/2"x 7" Brake Pads Outboard Drums, ABS anti-lock brake system
Tires _____	11R24.5 Radials
Wheels _____	10 Hole Disc, Hub Piloted
Wiring _____	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Paint _____	Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

BOGIE	OPTIONAL EQUIPMENT
-------	--------------------

Type 30/30 Spring Brakes _____	add 40 lbs.
Single Point (2 Spring) _____	add 665 lbs.
Air Ride (Watson Integra) _____	add 175 lbs.
Air Lift One Axle _____	add 135 lbs.
Pitts Lift Kit - Air Lift One Axle on a Single Point Suspension _____	add 95 lbs.
Add a Third Axle (spring ride) _____	add 1,800 lbs.
Add a Third Axle (air ride) _____	add 1,885 lbs.
11R.22.5 Tires _____	deduct 88 lbs.
425/60R22.5 Super Singles on Aluminum Disc Wheels _____	deduct 595 lbs.
Aluminum Wheels (outside polished) _____	
Onboard Electronic Scales (trailer only) (Vulcan or SI) _____	add 55 lbs.
Truck only (not installed) _____	
Auto I.D. transmitter for multiple trucks, trailers _____	
Onboard Air Scales (trailer only) _____	add 30 lbs.
Air Gauge In Sealed Box _____	

MISCELLANEOUS	
---------------	--

- | | |
|--|---|
| <ul style="list-style-type: none"> ○ Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel) add 40 lbs. ○ Headboard add 450 lbs. ○ Additional Length add 60 lbs. ○ Removable Riser in Lieu of Dead Bolster ○ Additional Winches (cables or straps) ○ 1/2" Kingpin Plate add 60 lbs. ○ Two-Speed Landing Gear deduct 165 lbs. ○ Grapple Deflectors <ul style="list-style-type: none"> ○ Standard Vertical Flat Bar Type - Center Section Only add 40 lbs. | <ul style="list-style-type: none"> ○ ">" Type - Deflects Grapple - Center Section Only add 85 lbs. ○ Grapple Bar off Rear Bumper 85 lbs. ○ 8' Wide Trailer deduct 100 lbs. ○ Moveable Bolsters 50 lbs. ○ Additional Bolsters 450 lbs. ○ Removable Standards ○ Additional Lights ○ Special Paint Color (Any Color Other Than Black) |
|--|---|