



Model LT40-8L

www.pittrailers.com

STANDARD FEATURES	LOAD PAYIN SERIES
Load Capacity	80,000 lbs.
Weight	9,400 lbs.
Overall Length	40'
Width	8'6"
King Pin Swing Radius	84"
King Pin Setting	20"
King Pin Area	Covered w/ Two Hinged Tool Boxes
Fifth Wheel Height	48"
Mainframe	24" Fabricated T1 Steel - 8" Drop Center
Cross Members	Channel Iron w/ "X" Members
Bumper	Extended Push Bumper, 4"x 6"x 102"
Drag Bar	Braced to Back Bolster
Bolsters	4"x 10"x 102", High Yield Steel
Standards	5"x 5", High Yield Steel, 13' Overall
Landing Gear	Heavy Duty Winch Back, 7" Foot
Air Tank	Covered
Winches	With Four 30' Straps
Suspension	Hutch, 3 Point Four Spring w/ 14,000 lbs. cap. Springs
Axles	25,000 lbs. cap. 77.5" Track, Auto Slack Adjusters, Type 30 Brake Chambers, 16 1/2"x 7" Brake Pads Outboard Drums, ABS anti-lock brake system
Tires	11R24.5 Radials
Wheels	10 Hole Disc, Hub Piloted
Wiring	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Paint	Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

BOGIE	OPTIONAL EQUIPMENT
Type 30/30 Spring Brakes	add 40 lbs.
Single Point (2 Spring) entire length of tandem covered with channel iron	add 800 lbs.
Air Ride entire length of tandem covered with channel iron	add 310 lbs.
Air Lift One Axle	add 135 lbs.
Pitts Lift Kit - Air Lift 1 Axle on a Single Point Suspension	add 95 lbs.
Add a Third Axle (spring ride)	add 1,800 lbs.
Add a Third Axle (air ride)	add 1,885 lbs.
11R.22.5 Tires	deduct 88 lbs.
425/60R22.5 Super Singles on Aluminum Disc Wheels	deduct 595 lbs.
Aluminum Wheels (outside polished)	deduct 280 lbs.
Tire Inflation System	
Onboard Electronic Scales (trailer only) (Vulcan or SI)	add 55 lbs.
Truck only (not installed)	
Auto I.D. transmitter for multiple trucks, trailers	
Onboard Air Scales (trailer only)	add 30 lbs.
Air Gauge In Sealed Box	

MISCELLANEOUS

- o Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel) add 40 lbs.
- o Headboard add 450 lbs.
- o Additional Length add 60 lbs. per ft.
- o Steel Fenders (Front Mud Guard)
 - o (Full Front Fender)
 - o (Rear Tandem Fender)
- o Additional Winches (Cables or Winches)
- o 1/2" Kingpin Plate add 60 lbs.
- o Two-Speed Landing Gear deduct 165 lbs.
- o Grapple Deflectors
 - o Standard Vertical Flat Bar Type - Center Section Only add 40 lbs.
 - o ">" Type - Deflects Grapple - Center Section Only add 85 lbs.
- o Grapple Bar off Rear Bumper add 85 lbs.
- o 8' Wide Trailer deduct 100 lbs.
- o Moveable Bolsters add 50 lbs..
- o Additional Bolsters add 450 lbs.
- o Removable Standards
- o Additional Lights
- o Special Paint Color (Any Color Other Than Black)