



PH. 800-321-8073

FX. 334-855-3507

Model HD35

www.pittstrailers.com

STANDARD FEATURES

Fabricated Mainframe

Load Capacity _____	70,000 lbs. In 16'
Weight _____	17,900 lbs.
Overall Length _____	50'
Width _____	8'6"
Deck Length _____	33' 6" (25' Flat Deck + 8'6" Tail)
Deck Height _____	35" Loaded
Gooseneck _____	Flat Deck-Wood with 17 Degree Slope -Steel with Traction Bars
Fifth Wheel Height _____	49"
King Pin Setting _____	18"
King Pin Swing Radius _____	84"
Mainframe _____	16" Fabricated with Positive Camber (Four I-Beam Design)
Siderails _____	14" Fabricated with Positive Camber (Four I-Beam Design)
Cross Members _____	8" Wide Flange-Mill Roll "I" Beam (On 20" Centers)
Wheel Wells _____	Covered with Check Plate & Traction Bars
Hydraulic Tail _____	Load Angle 14°, With Air Dumped 12.5°
Power Source _____	Set Up For Wet Line
Winch _____	20,000 lbs. with Wireless Remote
Landing Gear _____	2 Speed 50,000 lb. Capacity
Tool Box _____	Covered in Gooseneck
Lashing Rings _____	10 Per Side (20 total)
Decking _____	Full 1-3/4" Apitong
Suspension _____	Air Ride w/ Auto & Manual Controls, - 3/2" Down + 5" Up
Axles _____	25,000lb. cap. 77.5" Track, Auto Slack Adjusters, Type 30 Brake Chambers, outboard drums, ABS Anti Lock Brakes
Tires _____	235/75R17.5 Low Profile Radials
Wheels _____	6.75 x 17.5 Steel Disc
Brakes _____	12 1/4" x 7 1/2"
Wiring _____	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Flag Holders _____	In All Four Corners
Paint _____	Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE.

OPTIONAL EQUIPMENT GOOSENECK

- 12,000 lb. Winch _____
- Self Contained 13 H.P Honda Power Unit _____
- Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel) _____
- Hydraulic Motor Grader Ramps (to upper deck) _____
- 9° Aluminum "Paver" Approach Ramps _____
- 90° Gooseneck With Flat Upper Deck - Wood Filled _____

DECK

- Additional Length In Deck Area _____
- Additional Width 9' includes 83.5" Track Axles _____
- 10' includes 95.5" Track Axles _____
- Oak 1-3/4" (In Lieu of Apitong) _____
- Floor Clips (In Lieu of Screws) _____
- Widening Brackets _____

BOGIE

- Type 30/30 Spring Brakes (Per Axle) _____
- Single Point (2 Spring) _____
- Hutch, Three Point (4 Spring) _____
- Aluminum Wheels (Outside Polished) _____