



MODEL: 35-26

Model LB35-26

www.pittstrailers.com

STANDARD FEATURES	Fabricated Mainframe
-------------------	----------------------

Load Capacity _____	70,000 lbs. In 16'
Weight _____	16,900lbs.
Overall Length _____	45'
Width _____	8'6"
Deck Length _____	20' Cambered Deck
Deck Height _____	26" Loaded
Gooseneck _____	Fixed, Full Width, with Motor Grader Ramps
Fifth Wheel Height _____	48"
King Pin Swing Radius _____	84"
King Pin Setting _____	18"
Mainframe _____	14" Fabricated with Positive Camber (Four "T"-Beam Design)
Siderails _____	12" Fabricated with Positive Camber (Four "T"-Beam Design)
Cross Members _____	8" Wide Flange-Mill Roll "T" Beam
Wheel Wells _____	Covered with Check Plate & Traction Bars
Dovetail _____	36"- Covered with Check Plate and Traction Bars
Loading Ramps _____	Spring Assist, 24"x 72"
Landing Gear _____	Two Speed, 50,000 lbs. Capacity
Lashing Rings _____	8 Per Side (16 total)
Decking _____	Full 1-3/4" Oak
Suspension _____	Hutch Three Point, Four Spring, with 14,000 lbs. Cap. Spring
Axles _____	25,000 lbs. Capacity, 77.5" Track, Auto Slack Adjusters, Type 30 Brake Chambers, Outboard drums, ABS
Brakes _____	16 1/2" x 7"
Tires _____	255/70R22.5 Low Profile Radials
Wheels _____	8.25 x 22.5 Steel Disc/Hub Piloted
Wiring _____	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Tool Box _____	Covered In Gooseneck
Mud Flaps _____	Spray Guard and Anti-Sail
Flag Holders _____	On All Four Corners
Paint _____	Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

- Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel) _____
- 90° Gooseneck With Flat Upper Deck - Wood Filled _____

DECK

- Additional Length In Deck Area _____
- Additional Width 9' includes 83.5" Track Axles _____
- 10' includes 95.5" Track Axles _____
- Widening Brackets _____
- Apitong 1-3/4" (In Lieu of Oak) _____
- Floor Clips (In Lieu of Screws) _____

BOGIE

- Type 30/30 Spring Brakes (Per Axle)
- Aluminum Wheels (Outside Polished)
- Air Ride 50,000 lb. Cap.
- Single Point 50,000 lb. Cap.
- 48" Dovetail Covered with Check Plate & Traction Bars
- 60" Dovetail Covered with Check Plate & Traction Bars
- Rear Hydraulic Ramps (36"x 96")
- Double Folding (36"x 144")